



Cca

APPLICATION

The TOPSOLAR[®] PV H1Z2Z2-K cable, which is TÜV certified according to EN 50618 and AENOR certified according to IEC 62930, it is suitable for both fixed and mobile solar installations (solar farms, rooftop solar installations and floating plants).

It is a highly flexible cable compatible with all major connectors and specially designed for the connection of photovoltaic panels.

This versatile single-conductor cable is designed to meet the varying needs of the solar industry.

Suitable for wet, damp and humid locations.

- Solar PV installations string cable.

CONSTRUCTION

Conductor

Electrolytic annealed tinned copper conductor class 5 (flexible) according to IEC 60228 and EN 60228.

Insulation

Halogen free cross linked rubber insulation.

Insulation requirements according to table B1 in Annex B of EN 50618 and IEC 62930.

Outer sheath

Halogen free cross linked flexible rubber outer sheath.

Outer sheath requirements according to table B1 in Annex B of EN 50618 and IEC 62930.

Red or black colour.

CHARACTERISTICS



Electrical performance

Low voltage: 1,5/1,5 (1,8) kV DC.
1,0/1,0 kV AC.



Thermal performance

Maximum service temperature: 120°C during 20.000 h.
Maximum short-circuit temperature: 250°C (max. 5 s).
Minimum service temperature: -40°C (fixed and protected installations).



Fire performance

Flame non-propagation according to EN 60332-1-2 / IEC 60332-1-2.
Fire non-propagation according to EN 50399.
Reaction to fire CPR: C_{ca}-s1b, d2, a1, according to EN 50575.
LSHF (Low Smoke Halogen Free) according to EN 60754-1 / IEC 60754-1.
Low smoke emission according to EN 61034 / IEC 61034:
Light transmittance > 60%.
Low corrosive gases emission according to EN 60754-2 / IEC 60754-2.



Mechanical performance

Minimum bending radius:
4 x cable diameter (cable diameter ≤ 8 mm)
5 x cable diameter (8 < cable diameter ≤ 12 mm)
6 x cable diameter (cable diameter > 12 mm).
Impact resistance: AG2 Medium severity.



Environmental performance

Chemical & Oil resistance: Excellent.
Grease & mineral oils resistance: Excellent.
Ozone resistant according to EN 50618.
UV Resistant according to EN 50618.
Water resistance: AD8 Submersion.



Installation conditions

Open Air.
Buried.
In conduit.

STANDARDS / COMPLIANCE



According to
EN 50618/ IEC 62930 / UTE C 32-502




Standards and approvals
TÜV (from 2.5 to 25mm² in Black and Red) / RETIE
/ AENOR/ RoHS / CE



CPR (Construction Products Regulation)
C_{ca}-s1b, d2, a1



DIMENSIONS & ADMISSIBLE INTENSITIES



Cross-Section (mm ²)	Diameter (mm)	Weight (kg/km)	Single cable free in air (A)	Single cable on surfaces (A)	To cables adjacent on surface (A)	Voltage drop (V/A · km)
1 x 1,5	4,5	35	30	29	24	38,1
1 x 2,5	5,0	45	41	39	33	22,8
1 x 4	5,4	60	55	52	44	14,3
1 x 6	6,0	80	70	67	57	9,49
1 x 10	7,0	120	98	93	79	5,46
1 x 16	8,2	180	132	125	107	3,47
1 x 25	10,2	280	176	167	142	2,23
1 x 35	11,5	375	218	207	176	1,58
1 x 50	13,3	525	276	262	221	1,10
1 x 70	15,0	720	347	330	278	0,772
1 x 95	17,0	930	416	395	333	0,585
1 x 120	18,7	1.175	488	464	390	0,457
1 x 150	21,0	1.475	566	538	453	0,368
1 x 185	23,5	1.805	644	612	515	0,301
1 x 240	26,3	2.345	775	736	620	0,228

The tolerances on the nominal outer diameters are:

Cables with outer diameter $d \leq 7$ mm. → -0,1+0,2 mm

Cables with outer diameter $7 < d < 10$ mm. → -0,1+0,3 mm

Cables with outer diameter $d \geq 10$ mm. → -0,2+0,4 mm

Current-carrying capacities, in amperes, are according to EN 50618 (ambient temperature of 60 °C). In all cases it is supposed a direct current circuit. Voltage drop is calculated with conductor temperature of 120 °C.